

EXTERIOR

Construction

- Solid laminate hull and barrier coat to prevent against osmosis
- Hull with structured and glued inner mould
- Prisma Process® injected deck
- L-shaped cast iron keel
- Rudder with foam core and GRP skin, composite rudder shaft

Sails

- Mainsail (furling) 52,20 m² / 562 sq ft
- Furling genoa 110 % 55,90 m² / 601 sq ft

Mast and rigging

- Z-Spar deck-stepped, anodised aluminium in-mast furling mast, fractional rig
- Two levels of spreaders
- Anodised aluminium boom
- Facnor® genoa furler
- Rigid vang
- Standing rigging discontinuous made of stainless steel cable
- Running rigging: halyards and sheets in Dyneema®, additional lines and sheets in polyester

Sailing features

- Spinlock® line stoppers
- Harken® Genoa Tracks with genoa sheet cars
- Harken® turning blocks
- 1 Harken® 46.2 self-tailing winch
- 2 Harken® 60.2 self-tailing winches

Deck

- Open bow pulpit
- Double stainless steel lifelines
- Stainless steel double anchor roller
- Anchor windlass 1500 W
- Anchor locker with drain
- Mooring cleats (6)
- Sail locker access by opening deck hatch
- Opening deck hatches (8)
- Lateral coachroof windows
- Opening ports integrated into fixed windows (2)

Cockpit

- Two leather-covered stainless steel steering wheels
- Lounge chair on both sides of the companionway
- Cockpit table with integrated freezer
- Liferaft locker (L 0'3" x H 0'2" x 10'1" cm)
- 2 backstay chainplates
- Cockpit lockers (4)
- Gas locker (2 bottles)
- Large Teak aft fold-down swim platform
- Teak inlay on bench seats, steps, cockpit floor and transom platform
- Stainless steel handrails
- Shore power socket
- Drop-down companionway hatch

Forward sail locker

- Access via lockable deck hatch
- Access to bow thruster and technical areas
- LED lighting

INTERIOR

Saloon

- Seating arrangement on starboard (5 guests)
- Deep sofa to port
- Lockers above seating
- Hinged storage compartments under seatings
- Dining table with two fixed stainless steel legs
- LED lighting with dimmer
- Fixed hull ports (4)
- Flush opening hatches (4)
- Wine storage locker under floorboards

Galley

- U-shaped galley on starboard with Corian® counter top
- Double stainless steel sinks with covers
- Chrome mixer tap
- Drawers with shock absorbers and storage units
- Garbage bin integrated into countertop
- Gas cooker with 2 burners and oven
- 130 L / 34 US gal combination fridge / freezer 12 V
- Handrails
- Dust collector integrated into the floorboard

Utility room

- (standard / located between galley and starboard aft area)
- Hanging locker and storage cabinets

Aft head compartment (replaces the utility room)

- With double access from saloon and aft cabin
- Cabinet with sink and Corian® countertop
- Lacquered upper storage lockers
- LED overhead lighting
- Shower drain with switch
- Marine toilet with manual pump
- Mirror
- Clothes hook and towel bar

Chart table

- Ergonomic and seaworthy seat
- Chart table with opening compartment
- Upper storage compartment
- Bicolour reading light
- Navigation and level control screens

Forward cabins

Owner's stateroom

- Double berth (2,05 x 1,60 m / 6'8" x 5'2")
- Comfortable seats
- Double hanging locker with drawers (4)
- Upper compartments with assisted opening
- Drawers under berth (2)
- LED reading lights and roof lights
- Bedside tables
- Fixed hull ports with aviation shades (2)
- Deck hatches (2)
- En-suite toilet / shower compartment

Aft cabins

Port VIP cabin

- Double berth (2,02 x 1,60 m / 6'7" x 5'2")
- Hanging locker
- Opening storage lockers to each side of the berth
- LED reading lights and roof lights
- Bedside tables
- Fixed portholes with solid sliding blind
- Opening port
- En-suite toilet / shower compartment

Workshop

(standard / located on aft starboard and accessible from the interior or from the cockpit)

- Direct access to the cockpit via a stainless steel ladder
- Storage locker and shelving
- Resistant laminated plywood on the top of the carpentry

Skipper cabin

(replaces workshop)

- Single berth (2,00 x 0,70 m / 6'6" x 2'3")
- Direct access to the cockpit via a stainless steel ladder
- Hanging locker
- Storage locker with removable plastic baskets
- Shelving along hull with stainless steel rail to attach lines
- Indirect LED lighting
- Opening port

Guest cabin

(replaces workshop)

- Double berth (2,00 x 1,40 m / 6'6" x 4'7")
- Hanging locker
- Indirect LED lighting
- Opening port

TECHNICAL EQUIPMENTS

Electric

- Main electric panel at navigation station, backlit in a soft blue light
- Switches for domestic systems
- 12 V accessory plug
- LCD displays: DC Voltage level, amperage consumption meter, fuel and water indicators
- House battery bank (4 x 115 Ah / 12 V)
- Engine battery bank (1 x 120 Ah / 12 V)
- Engine alternator 125 Ah
- Battery switches: in compartment to starboard of the companionway
- 230 V or 115 V plugs in each cabin, saloon, galley and at the chart table
- LED lightings
- SEANAPPS connected technology: allows you to monitor the condition of the boat and receive alerts and maintenance recommendations via the associated mobile application. Depending on the boat's configuration, SEANAPPS collects safety indicators (GPS position, battery status, bilge level, engine

status), navigation data (distance travelled, speed, depth), and comfort information (tank levels, cabin temperature and humidity).

Motorization

- YANMAR® 4JH80CR Sail Drive 80 HP - 59 kW
- Soundproof engine room
- GRP engine bed and liner
- Fixed 3-blade propeller
- Roto-moulded exhaust box and stainless steel exhaust fitting on hull
- Extractor fan located in engine room
- Ventilation ducting vents on transom
- Roto-moulded fuel tank 240 L / 63 US gal
- Fuel / water separator
- Fuel gauge at electrical panel

Plumbing

Fresh water

- Fresh water system with high-pressure 12 V pump (19 L / min or 5 US gal / min), inline filter and accumulator tank
- 400 L / 106 US gal tank under the forward berth
- 240 L / 63 US gal tank under aft cabin berth
- Tank gauges (1 per tank)
- Tank manifold with selector valves
- 40 L / 11 US gal hot water heater
- Hot and cold cockpit shower

Raw and waste waters

- Fresh water system with high-pressure 12 V pump (19 L / min or 5 US gal / min), inline filter and accumulator tank
- 400 L / 106 US gal tank under the forward berth
- 240 L / 63 US gal tank under aft cabin berth
- Tank gauges (1 per tank)
- Tank manifold with selector valves
- 40 L / 11 US gal hot water heater
- Hot and cold cockpit shower

Bilge drainage

- Automatic electric bilge pump
- Manual bilge pump accessible in the cockpit

HEADROOM

- Master forward cabin 2,01 m / 6'7"
- Aft guest's cabin(s) 1,90 m / 6'2"
- Companionway 2,05 m / 6'8"
- Galley 2,10 m / 6'10"
- Utility room 1,97 m / 6'5"
- Forward owner's head 2,03 m / 6'7"
- Aft guest's head 2,06 m / 6'9"