

EXTERIOR

Construction

- Solid laminate hull and barrier coat to prevent against osmosis
- Hull with structured and glued inner mould
- Prisma Process® injected deck
- L-shaped cast iron keel
- Rudder with foam core and GRP skin, composite rudder shaft

Sails

- Standard mainsail (furling) 48 m² / 516 sq ft
- Standard genoa 109 % 63 m² / 678 sq ft

Mast and rigging

- Deck-stepped, anodised aluminium in-mast furling mast, fractional rig built by Z-Spar
- Double spreader design
- Anodised aluminium boom
- Facnor® genoa furler
- Rigid boom vang
- Standing rigging made of discontinuous stainless steel cable
- Running rigging: halyards and sheets in Dyneema, additional lines and sheets in polyester

Sailing features

- Spinlock® line stoppers
- Harken® Genoa Tracks with genoa sheet cars
- Harken® turning blocks
- 2 Harken® 46.2 ST winches
- 2 Harken® 70.2 ST winches

Deck

- Open bow pulpit
- Double stainless steel lifelines
- Stainless steel double anchor roller
- Anchor windlass 1500 W
- Anchor locker with drain
- Mooring cleats (6)
- Sail locker access
- Opening deck hatches (10)
- Lateral coachroof windows
- Opening ports integrated behind fixed windows (2)
- Main chainplates in stainless steel at deck edge
- Folding padeyes on deck

Cockpit

- Double leather-covered stainless steel steering wheels
- Lounge chair on both sides of the companionway
- Cockpit table with integrated freezer
- Liferaft locker
- 2 backstay chainplates
- Cockpit lockers (4)
- Gas locker (2 bottles)
- Large Teak aft fold-down swim platform
- Teak inlay on bench seats, cockpit floor, steps and transom platform
- Stainless steel handrail
- Shore power socket
- Drop-down companionway hatch (plexiglass)

Sail locker forward

- Access through lockable deck hatch
- Access ladder
- Shelving along hull sides for storage
- Access to bow thruster and technical areas
- LED lighting

INTERIOR

Saloon

- Seating arrangement on starboard (7 guests)
- Overhead lockers above seating
- Hinged storage compartments under seatings
- Saloon table with two removable legs convertible to double berth
- Short legs, saloon backrest to be used as mattress for double berth
- LED lighting with dimmer
- Fixed hull ports (2)
- Low-profile opening hatches (4)

Galley

- Long galley to port with Corian® counter top
- or
- Aft galley to starboard with Corian® counter top
- Double stainless steel sinks with removable covers
- Chromed mixer tap
- Foot pump with separate tap, Y-valve to select fresh or sea water
- Drawers with shock absorbers and storage units
- Retractable waste bin
- Gas oven cooker with 2 burners with removable top counter
- 250 L / 66 US gal combination fridge / freezer 12 V
- Handrails
- Dust pan integrated into the floorboard

Utility room

- (standard / located between galley and starboard aft area)
- Hanging locker and storage cabinets

Chart table

- Ergonomic and seaworthy seat
- Chart table with opening compartment
- Upper storage compartment
- Bicolour reading light
- Navigation and level control screens

Forward cabins

Owner's stateroom

- Double berth (2,03 x 1,60 m / 6'7" x 5'2")
- Lateral bunks
- Hanging locker with storage drawers (4)
- Assisted opening storage cabinet
- Storage drawers under berth (2)
- LED reading lights and lighting
- Bedside tables
- Fixed hull ports with sliding shades (2)
- Deck hatches (4)
- En-suite toilet / shower room

Double symmetrical modular cabins

- Double berth (2,03 m x 1,56 m / 6'7" x 5'1")
- Removable bulkhead, to be stored under the beds
- Double hanging locker with storage lockers
- Upper storage cabinet under the side decks
- Under-bed storage
- AC and USB plugs
- LED reading lights and lighting
- Fixed hull ports with aviation shades (2)
- Opening deck hatches (2)
- En-suite toilet / shower compartment

Aft cabins

Port VIP cabin

- Double berth (2,03 m x 1,50 m / 6'7" x 4'11")
- Sofa
- Hanging locker
- LED reading lights and lighting
- Bedside tables
- Fixed hull port with aviation shade
- Opening ports (2)
- En-suite toilet / shower room

Starboard guest cabin

- 2 single berths (2,05 x 0,70 m / 6'8" x 2'3")
- Hanging locker
- Indirect LED lighting
- Opening ports (2)
- En-suite toilet / shower room

Starboard side cabin

- Twin bunk (2,05 m x 0,70 m / 6'5" x 2'3")
- Hanging locker with shelving
- Under-bed storage
- LED reading lights and lighting
- Opening port

TECHNICAL EQUIPMENTS

Electric

- Main electric panel at navigation station backlit with a soft blue light
- Switches for domestic systems
- 12 V plug
- LCD displays: DC Voltage level, amperage consumption meter, fuel and water gauges
- House batteries bank (4 x 115 Ah / 12 V)
- Engine battery bank (1 x 120 Ah / 12 V)
- Engine alternator 12V / 125 Ah
- Battery switches: in compartment to starboard of the companionway
- 12 V and 230 V or 115 V plugs in each cabin, saloon, galley and at chart table
- LED lightings
- SEANAPPS connected technology: allows you to monitor the condition of the boat and receive alerts and maintenance recommendations via the associated mobile application. Depending on the boat's

configuration, SEANAPPS collects safety indicators (GPS position, battery status, bilge level, engine status), navigation data (distance travelled, speed, depth), and comfort information (tank levels, cabin temperature and humidity).

Motorization

- YANMAR® 4JH4TCE Sail Drive 80 HP - 59 kW
- Sound insulation
- GRP engine bed and liner
- Fixed 3-blade propeller
- Roto moulded exhaust box, stainless steel exhaust fitting on hull
- Extractor fan located in engine room
- Ventilation ducting vents on transom
- Roto moulded tank 240 L / 63 US gal
- Inline fuel / water separator
- Fuel gauge at electrical panel

Plumbing

- Fresh water
- Fresh water system, high-pressure 12V pump (19 L/min or 5 US gal / min), inline filter and accumulator tank
 - 400 L / 106 US gal tank under the forward berth
 - 240 L / 63 US gal tank under aft cabin berth
 - Tank gauges (1 per tank)
 - Manifold to select the water tanks
 - 40 L / 11 US gal hot water heater
 - Hot and cold cockpit shower

Raw and waste waters

- Shower pumps with macerator, shower pumps switch
- Sinks and washbasins directly drained overboard
- Manual marine toilets with large bowl
- Roto moulded holding tank 85 L / 22 US gal in each head
- Hoses built in high quality White PCV

Bilge drainage

- Automatic electric bilge pump with manual switch at ythe electrical panel
- Manual bilge pump located in cockpit

HEADROOM

- Master forward cabin 1,98 m / 6'6"
- Aft guest's cabin(s) 1,97 m / 6'6"
- Aft VIP's cabin(s) 1,97 m / 6'6"
- Companionway 2,07 m / 6'9"
- Galley 2,05 m / 6'9"
- Forward owner's head 2,02 m / 6'8"
- Aft VIP's head 2,13 m / 6'0"