



JEANNEAU

SEA LOFT 480

SPECIFICATIONS

Overall length	14,85 m	48'7"
Waterline length	14,00 m	45'9"
Beam	4,50 m	14'8"
Displacement light load	10 900 kg	24 030 bs
Draft	0,98 m	3'21"
Fuel capacity	200 L	53 US gal
Water capacity	580 L	153 US gal
Fridge capacity	288 L	78 US gal
Holding tank capacity	180 L	47 US gal
CE category CE	CE B10 / C18 / D18	
Architect / Designer	Marc Lombard Yacht Design - Jeanneau Design	



AN EXCEPTIONAL LEVEL OF EQUIPMENT

EXTERIOR

Construction

- Infused sandwich hull with balsa core and fiberglass skins, ISO gelcoat surface, protective barrier coat
- Counter mold for "monohull" part and plywood partition for "catamaran" part
- Infused sandwich deck and contact counter mold
- Twin rudders connected by a connecting rod and a hydraulic steering system

Cockpit

- 1 cockpit table
- 2 movable sofas
- Leather-covered stainless steel steering wheel
- Telescopic bath ladder
- Hinged companionway doors
- Fully equipped island galley
- Electric davits for dinghy

Deck

- Easy circulation thanks to the side decks
- Deck hatches
- Mid-ship cleats
- Electric windlass

INTERIOR

- One-level interior with no door sills
- LED lighting
- Large double berths
- Blinds for each hatch and opening in the forward and aft cabins

TECHNICAL

Electrical

- LED navigation and anchoring lights
- 12 V electrical panel
- Victron battery
- 90 Ah alternator and charge distributor/isolator
- Positive and negative battery cut-off switches to better protect battery banks

Water System

- Hot and cold cockpit shower
- Hot water heater 60 L / 15 US gal
- "Heavy-duty" water pump

Engine

- Yanmar engines 2x45HP shaft drive
- Fixed propeller
- Sound insulation 40 mm / 1 1/2" thick, with fire retardant film



EXTERIOR AND TECHNICAL EQUIPMENT

COCKPIT

Standard

- Large cockpit table for 8 people
- Chairs (8)
- Cockpit lockers for storage (8)
- Engine access in the cockpit (2)
- Universal gas box, cut-off valve under the sink
- Steering wheels with leather wrap
- Engine controls: throttle levers at helm station
- 2 huge manual opening terraces
- Hinged companionway doors in plexiglass
- Sliding horizontal hatch in plexiglass
- Telescopic swim ladder on the aft port platform
- Hardtop with integrated windshield
- 12x Marlex solar panels Marlex 400W (total 4,8kW)
- Electric lateral blinds (transparent or batyline)
- Cockpit floor in Polyester
- Transparent electric side cockpit curtains

Options

- Micro-perforated electric side cockpit curtains
- Cockpit floor in Marinemat
- Fishing rod holders (x4)
- Electrical davit for dinghy
- 26" TV pre-fitting in cockpit

GALLEY

Standard

- Island galley
- Countertop in Corian
- Stainless steel sink
- Oven
- 2 gaz burners
- 2 fridges 38 US gal (76 US gal in total)
- Gaz plancha
- Upper storages

Options

- Ice maker
- Dishwasher for 6

FRONT DECK

Standard

- Sunbed on the foredeck for 3
- Bench with cup holders
- Storage locker
- Integrated bowsprit with anchor roller

Options

- Removable sun shade on carbon legs
- Skipper cabin instead of the storage locker

DECK HARDWARE

Standard

- 6 aluminium mooring cleats
- Deep anchor locker
- Electric 12 V Lofrans windlass 1 000 W
- Large, fixed hull ports (4)
- Opening deck hatches (2)

LIGHTING

Standard

- LED interior lighting

ELECTRICAL

Standard

- Main 12 V electrical panel on starboard side next to the companionway, domestic switches, USB plug
- 12V Circuit for house and engine system
- Domestic battery bank capacity 3 x 95 Ah / 12 V
- Engine start battery capacity 1 x 50 Ah / 12 V
- 12 V engine alternator: 90 Ah
- Positive and negative battery switches 12 V in the central cockpit locker
- Inverter 12 V > 220 V 2 000 W enable to use 220 V appliance from the domestic battery bank
- SEANAPPS connected technology: allows you to monitor the condition of the boat and receive alerts and maintenance recommendations via the associated mobile application. Depending on the boat's configuration, SEANAPPS collects safety indicators (GPS position, battery status, bilge level, engine status), navigation data (distance travelled, speed, depth), and comfort information (tank levels, cabin temperature and humidity).

PLUMBING

FRESH WATER

- Pressurised water distributed through-out the boat via semi-rigid hose
- "Heavy-duty" water pump 36 L / 9 US gal / mn, accumulator tank for consistent water pressure
- Water tanks: 380 L / 100 US gal, and 200 L (total 580 L)
- Tank gauges (1 per tank)
- Water boiler 60 L / 16 US gal connected to the engine and 220 V circuit
- Hot and cold cockpit shower on transom

GREY AND BLACK WATER

- Automatic electrical shower self-activating

- Electrical WC

- Black water tank 50 L / 13 US gal, with gravity drain and deck fitting (skipper cabin)
- Black water tank 80 L / 21 US gal, with gravity drain and deck fitting (lateral heads)

BILGES DRAINAGE

- Electric bilge pumps located in bilge areas with activation via switch at electrical panel
- Dual-action manual bilge pumps located in the cockpit, with separate hose from primary bilge pumps

GAS

- Gas leakage detector

ENGINE

Standard

- 2x Yanmar Engine 4JH45CR Shaft Drive - 2x45 HP / 33 kW - Alternator 90 Ah
- Fixed propellers
- Insulation: Foam 40 mm, with fire retardant film
- Built-in muffler, air ventilation and stainless steel exhaust fitting
- Ventilation system extractor fan located near the engine, benefiting from the insulation of the engine room. Outlets vents at the back of cockpit
- Roto moulded fuel tank 200 L / 53 US gal located under the aft cabin berth, fuel / water separator
- Accesss to engines by cockpit lockers
- Tunnel bow thruster 100 kW with 4x 12V 50AH batteries Excide

Option

- Electrical engines : 2x POD 10kW Fischer Panda, includes DC 48V 22KW generator

INTERIOR EQUIPMENT AND LAYOUTS



Version A

2 forward cabins,
2 aft cabins / 4 heads

Version B

Front owners cabin,
2 aft cabins / 2 heads

WOODWORK

Standard

- Lindberg laminated oak floorboard
- Charter woodwork in laminated wood Laos Teck

HELM STATION

Standard

- Leather-covered stainless steel steering wheel
- Engine throttles at helm station
- Compass
- USB plugs (2)
- FUSION audio system with RA210 display
- Removable footrest
- Electronics : Raymarine AXIOM 12" display, Next4 9" display (Supervision), Loch speedo Raymarine I70, Raymarine auto-pilot P70, VHF 73 Raymarine

COMFORT

Standard

- Cushions in High Density foam 120 mm in the salon
- High Density Premium mattresses in cabins

Option

- Air conditioning reversible working on batteries or shore power with 2 units (23 000 BTU in total)

TWIN FORWARD CABINS

(version A)

- Large rectangular berth 2,00 x 1,9/1,15m / 6'6" x 6'4"/5'7"
- Hanging locker
- 1 spotlight and 1 LED strip
- Opening deck hatch with ventilation
- Large hull windows with opening porthole and shading
- Blinds and bugs screens for deck hatches
- Forward heads: Wooden washbasin cabinet, storage cupboard, deck panel, indirect LED lighting and spotlight, shower, shower drain pump with automatic timed activation, valves and fittings under the washbasin cabinet, large marine toilet with electric pump, coat hook

FORWARD OWNER'S CABIN

(version B)

Standard

- Island bed 2,00 x 1,60 m / 6'6" x 5'2"
- Hanging locker
- Cabinet in the entrance
- LED Lighting and 2 spotlights
- LED reading lights with USB plug
- Large hull windows on both sides with opening porthole and blinds
- Blinds for each opening
- Owner's head: Wooden washbasin cabinet, storage cupboard, deck panel, indirect LED lighting and spotlights, separated shower, shower drain pump with automatic timed activation, valves and connections under the washbasin cabinet, large marine toilet with electric pump, coat hook

AFT CABIN(S) (all versions)

- Large berth 2,00 x 1,56 m / 6'6" x 5'11"
- Hanging locker storage and shelf along hull
- LED Lighting
- LED reading lights
- Large hull window with an opening porthole
- Blinds for each opening
- Access to tanks and technical area
- Salles d'eau arrière: Wooden washbasin cabinet, storage cupboard, deck panel, indirect LED lighting and spotlights, shower, shower drain pump with automatic timed activation, valves and connections under the washbasin cabinet, large marine toilet with electric pump, coat hook

SKIPPER CABIN (option)

- Berth 1,90m x 0,70m / 6'2" x 2'3"
- Marine WC
- Sink under the bed

HEADROOM

Forward cabin(s)	2,00 m	6'8"
Aft cabin(s)	2,00 m	6'6"
Companionway	2,00 m	6'6"
Saloon	2,00 m	6'6"
Galley	2,00 m	6'6"
Forward head	2,00 m	6'6"
Aft head	1,99 m	6'5"

