## Model year 2010 SUN OPYSSEY

## Sun Odyssey 44i

















Sails







Certification	n conform with CE regulation.	SO 44i	SO 44i Performance	SO 49i	SO 49i Performance
	Overall length	13,75 m	13,75 m	15,07 m	15,07 m
	Hull length	13,41 m	13,41 m	14,75 m	14,75 m
	Waterline length	11,45 m	11,45 m	12,98 m	12,98 m
	Beam	4,37 m	4,37 m	4,49 m	4,49 m
	Displacement light load with deep draft keel	9930 kg	9930 kg	12600 kg	12600 kg
	<b>Standard draft</b> cast iron fin keel with elongated bulb and exterior epoxy barrier coat	2,05 m	2,05 m	2,15 m	2,15 m
su	Standard keel weight	2954 kg	2954 kg	3750 kg	3750 kg
Specifications	Shoal draft cast iron fin keel with elongated bulb and exterior epoxy barrier coat	1,65 m	-	1,69 m	-
	Shoal keel weight	3160 kg	-	4100 kg	-
	<b>Performance keel draft</b> cast iron fin keel with elongated bulb and exterior epoxy barrier coat, profiled leading and trailing edges	-	2,30 m	-	2,35 m
g	Performance keel weight	-	2865 kg	-	3640 kg
	CE category	A10-B12-C14	A10-B12-C14	A10-B12-C14	A10-B12-C14
	Architect / Designer	P. Briand	P. Briand	P. Briand	P. Briand
	Water 2 rotomolded tanks located under forward and aft berths with seperate deck fills	615 L	615 L	615 L	615 L
	Fuel rotomolded tank located under aft berth with deck fill	240 L	240 L	240 L	240 L
	<b>Holding tank</b> rotomolded tank located in head compartment with valve for overboard discharge via gravity and deck fitting for pump out	85 L	85 L	85 L	85 L
	<b>Fridge</b> fibreglass fridge compartment with 2 separate compartments and vertical access	255 L	255 L	255 L	255 L
	<b>Fridge</b> fibreglass fridge compartment with 2 separate compartments and vertical access	255 L	255 L	255 L	255 L

Classic mainsail 80% battened, high-tenacity Dacron cloth, Rutgerson® stainless steel eyes and 2 auto reefs	47,6 m²	-	-	-
Classic mainsail 100% battened, high-tenacity Dacron cloth, Rutgerson® stainless steel eyes and 2 auto reefs	-	-	49,2 m <sup>2</sup>	-
Furling genoa 140% high-tenacity Dacron cloth, Sunbrella® UV luff protection, Rutgerson® stainless steel eyes	53 m²	-	62,1 m <sup>2</sup>	
Performance mainsail full-batten, Prestige series tri-radial with sandwich construction of double taffeta layers				
and Mylar for form stability and Rutgerson® rolling cars, 2 automatic reefs and a 3 <sup>rd</sup> classic reef point	-	52 m²	-	55 m²
Performance furling genoa 145% tri-radial Prestige series with sandwich constructions of double taffeta layers				
and Mylar for form stability and Sunbrella® UV luff protection, Rutgerson® stainless steel eyes	-	52,2 m <sup>2</sup>	-	67 m²
Furling mainsail (optional) high-tenacity Dacron cloth, Sunbrella® UV luff protection, Rutgerson® stainless steel eyes	36,9 m²	-	39 m²	-
Spinnaker optimal size for boat (not available from Jeanneau)	120 m <sup>2</sup>	128 m²	141 m²	162 m²
Total sail area for standard mast and sails	100,6 m <sup>2</sup>	104,2 m <sup>2</sup>	111,3 m²	122 m²

lacktriangle Standard  $\Box$  Option - Not available

		SO 44i	SO 44i Performance	SO 49i	SO 49i
	Lazy bag in Sunrella® Captain Navy fabric with integrated lazy jacks		Тегротпинес		T er joinnairee
Sail Handling	<b>Genoa winches</b> 2 x Harken 50.2 self-tailing winches	•	•	-	-
	Genoa winches 2 x Harken 60.2 self-tailing winches	-	-		
	Coachroof winches 2 x Harken 46.2 self-tailing winches			_	
	Electric genoa winches 2 x Harken 50.2 STCE-H 12v self-tailing in place of standard winches  Electric genoa winches 2 x Harken 60.2 STCE-H 12v self-tailing in place of standard winches			-	- -
	Electric coachroof winch 1 x Harken 46.2 STCE-H 12v self-tailing in place of standard winch to port	PREFERENCE	PREFERENCE	PREFERENCE	PREFERENCE
	Genoa tracks adjustable Harken lead cars	•			•
	Winch handles 2 x Harken handles with ball-bearing grip				
	Line jammers Spinlock, on both sides of coachroof with Harken return blocks	•	•		•
	Mainsheet traveller long, roof-mounted Harken traveller with ball-bearing cars, control lines lead aft to cockpit	•	_		_
	Padeyes 3 Wichard on each side for spinnaker turning blocks, tweaker lines, pole downhaul  Spinnaker deck hardware triple Spinlock jammer to starboard, and an additional 3-sheave return block on deck				
	Asymmetrical spinnaker gear halyard, 2 sheets, tack line lead forward on deck, reinforced fitting on anchor roller, 3 Harken blocks	_			
	Symmetrical spinnaker gear halyard, 2 sheets, 2 guys, pole uphaul and downhaul, spinnaker pole and adjustable car for mast, Harken blocks				
	Classic mast aluminium with double spreaders, spinnaker track mounted forward and folding mast steps	•	-	•	
	Performance mast aluminium with double spreaders, spinnaker track mounted forward and folding mast steps	-		_	•
	Standing rigging discontinuous 1x19 stainless steel wire  Standing rigging discontinuous Dyform® stainless steel wire				
Bu	Backstay fixed, double	•	-	•	-
ggi	Backstay adjustable via a block and tackle system and bridle-mounted car	-		-	
Z P	Genoa furler with attachment to stemhead fitting and furling line lead aft to roof winch	•	-	•	-
Mast and Rigging	<b>Genoa furler</b> Facnor® racing series with removable drum, double sail slot and aerodynamic profile, mounted to stemhead fittings				
last	with short link plates to maximise sail area, furling line lead aft to roof winch	-		-	
>	Running rigging polyester topping lift, mainsail halyard, genoa halyard, mainsheet, genoa sheets	•	-	•	-
	Running rigging Dyneema® mainsail halyard, genoa halyard, mainsheet, genoa sheets  Rigid boom vang with gas cylinder and control line lead aft to the cockpit	-			
	Releasable forestay for storm sail, attaches to padeye in front of the anchor locker, stay is equipped with quick release	-		•••	•
	and adjustment mechanism, inner stay is attached to a padeye on starboard side deck when not in use				
		1			
	Teak inlay on seating area, transom and transom steps  Teak cockpit floor inlay				
	Teak side decks hand-laid teak side decks				
	Cockpit lockers 2 lockers under bench seats and 2 lazerette lockers under the helm seats for technical access to steering system				
	<b>Cockpit table</b> folding injected fibreglass table with storage, cup holders, bottle holders, stainless steel handrail, courtesy lighting,				
	12v plug, table base provides light, headroom and ventilation to aft cabins	•		_	•
o o	<b>Teak cockpit table</b> with all the same functions of above, standard table but with teak leaves and top, Sumbrella® Captain Navy cover	PREFERENCE	PREFERENCE	PREFERENCE	PREFERENCE
rag	Gas locker located outboard of port helm, room for 2 gas bottles with connection to gas system and cut-off valve under stove in the galley  Large storage locker under cockpit floor (location for optional generator)				
Sto	<b>Wheels</b> 2 leather-covered steering wheels with fibreglass pedestals with handrail, cup holders, compasses and easy access to winches				
eck	Steering wheel covers Sunbrella® Captain Navy blue with zips for easy removal				
D.	Transom gate double fibreglass doors that can be secured when open or closed	•	•	•	•
Cockpit & Deck Storage	Instrumentation dedicated space for instruments within easy reach of helm positions, room for GPS chartplotter mounted				
ckp	at aft end of cockpit table with easy viewing from each helm	•			
ပိ	Engine controls throttle and engine control panel mounted at starboard helm, engine panel, RPM gauge, warning lights, ignition	•		_	
	Swim ladder stainless steel folding ladder mounted on swim platform				
	Cockpit shower retractable hot and cold water shower with tap  Cockpit cushions Sunbrella® Captain Navy cushions for seating area with attachment clips				
	Cockpit bimini Sunbrella® Captain Navy with stainless steel bows, retractable with storage cover				
	Cockpit sprayhood wide Sunbrella® Captain Navy with vinyl windscreen with zip-out middle window for ventilation, retractable				
	Anchor locker forward, lockable, room for anchor and tackle, integrated windlass area, holder for windlass handle	•		•	•
	Deep sail locker forward, accessible via opening deck hatch with lock, stainless steel ladder, lighting	-	-		
	Short Performance bow pulpit stainless steel			-	-
	Stern pulpits stainless steel with flag holder, buoy bracket			•	
Deck Hardware	Outboard engine bracket mounted on stern pulpit				
	Windlass Quick 1000W combination rope and chain 10mm, vertical-mounted in the anchor locker, hand-held remote, manual handle				-
	Windlass LEWMAR 1500W combination rope and chain 12mm, vertical-mounted in the anchor locker with above-deck line drum, hand-held remote, manual handle	-	-	•	•
	Windlass control second windlass control mounted in cockpit with chain counter for easy, short-handed anchoring				
	Anchor roller double stainless steel fitting with self-launching roller for hands-free launching and retrieving			•	•
	Anchoring kit Delta anchor 20kg with 32 meters of 10mm chain and 45 meters of 18mm line  Anchoring kit Delta anchor 25kg with 40 meters of 12mm chain and 50 meters of 22mm line			-	-
	Lifelines double level of stainless steel lifelines with PVC coating, stainless steel stanchions with open gates		-		
	Toerail teak profile with integrated stainless steel chocks and drainage for side deck	•			
	Cleats 6 x aluminium mooring cleats				
	Rubrail for hull protection		_	_	_

		SO 44i		SO 49i		
		3C/2H	3C/3H	4C/2H	3C/2H	4C/4H
	Fine Teak® interior laminated panels with solid wood trim around galley, companionway and cabinetry, finished in satin UV stabilised varnish					
Poo/M	Laminate florboards with light-coloured lines, varnished edges		-	-	•	•
	PREMIUM matresses available on all berths, provides the ultimate in comfort					
	Forward owner's cabin with central berth and reading lights at head of berth					•
	Double berth with trim, PREMIUM mattress	2.00-1.50 m	2,00-1,50 m	-	2,02-1,60 m	_
	Mattress battens under high-density foam mattress for increased comfort			-		-
	Cushioned seat			_		_
	Storage under berth			-		_
	Large hanging locker					
	Vanity in forward cabin with desk, mirror, and lighting					
	, ,	-		-	_	-
cabin	Wood and white upholstered panels along hull	_	_	-		-
rsc	Storage lockers along hull sides with gas lifters and indirect lighting underneath	•	_	-	_	-
Forward owner's	Private forward owner's head compartment with sink, separate shower with plexiglass door, mirror, towel holder, toilet paper holder,	_				
rd o	wastebasket, cabinet above sink and shower sump with grate and electric drainage pump			-		-
rwa	Twin forward cabins transformable into single cabin by removable longitudinal bulkhead	-	-	_	-	
5	Double berths, PREMIUM mattresses	-	-	2,02 m-1,35 m	-	2,06 m-1,45 m
	Storage under berth	-	-	•	-	•
	Hanging lockers	-	-		-	
	Storage lockers along hull sides with gas lifters and indirect lighting underneath	-	-	•	-	•
	Bunk beds in forward cabin, removable	-	-		-	-
	Fabric hull liner	-	-		-	•
	2 head compartments forward with sink, shower, mirror, towel holder, toilet paper holder, wastebasket, cabinet above					
	sink and shower sump with grate and electric drainage pump	-	-	-	-	
Twin aft cabins	Twin aft cabins		•			••••••
	Double berths, PREMIUM mattresses	2 x 2 02 m-1 5 m	2 x 2.02 m-1.5 m		2 x 2.02 m - 1.5 m	2 x 2,02 m - 1,50 m
	Deep cabinet with shelves and hanging rod per cabin				- X 2.02 III 710 III	= 1,00 m
ins	Storage compartments along hull with indirect lighting underneath and open hanging lockers to either side of berth					
Twin aft cabins	Wood and white upholstered panels along hull		_	_		
n afi	<u> </u>	-	_	_	-	_
Twi	Head compartment aft with sink, shower, mirror, towel holder, toilet paper holder, wastebasket, shower sump,					
	with grate and electric drainage pump, access from aft cabin and saloon		-	-	_	-
	2 head compartments aft with sink, shower, mirror, towel holder, toilet paper holder, wastebasket, cabinet above sink		_	_		_
	and shower sump with grate and electric drainage pump access from aft cabins and saloon	-			- 	_
uo	Navigation station full-function with general electrical panel					
station	Lateral navigation desk with cushioned stool	-	•	•	-	•
rtion	Navigation desk with roll-away top and pass-through for plugs to facilitate the use of a laptop computer		-	-		-
Navigation	Leather-wrapped stainless steel handrail and leather-lined pen holder	-	-	-		-
z	Large storage drawer with divider under nav station/bar cabinet		-	-		-
	Saloon with U-shaped seating area to starboard, wrap-around cushions and storage under seating area					
	Saloon dining table with fiddles, removable pedestal legs and built-in bottle locker					
	Split cushion to fit over saloon table and support to turn standard table into a double berth					
	Deluxe saloon table with fixed storage base, inlayed table top, and folding leaves					
uo	Fixed bench seat facing table with cushion and leather-wrapped handrail					
Saloon	2 removable luxury armchairs with tiedowns for saloon (instead of bench seat)					
	Upper storage cabinets		•		•	
	Storage cabinet along hull					
	Indirect lighting under sidedecks	•	•	_	•	•
	Companionway made of laminate and solid wood trim with curved, hingred for access to engine, leather-wrapped handrails to either side					
	Galley with double sinks with covers and reversible cutting board, solid surface countertops, chrome plumbing fittings, storage cabinets and drawers	_		<u>-</u>		<del>-</del>
	Longitudinal galley					
	Dish draining compartment with cover					
<u>~</u>	Gimballed 2-burner stove with oven with stainless steel protection bar					
Galley	3-burner stainless steel stove with thermostatically controlled oven and stainless steel protection bar, in place of regular stove/oven unit	_	_	PREMIERE	PREMIERE	PREMIERE
	Double fridge box, top-loading with 2 opening lids, storage bins, 12v refrigeration and gas lift for door in large box and compressor	, NEWILL	- INCITICINE	TALTHERE	TALTITLAL	TALTILIAL
	L2v freezer unit for smaller fridge box with separate compressor	DDEMIEDE	PREMIERE	DDEWIEDE	PREMIERE	PREMIERE
			PREFERENCE			
i	Stainless steel vertical access door to large fridge box, includes wire shelving inside fridge box for increased storage	FREFERENCE	***************************************	rkerekence	PREFERENCE	PREFERENCE
moo.	Forward cabin (s)		1,90 m			2 m
	Aft cabin (s)			1,9		
			1,95 m			4
adroo	Companionway				-	4 m
Headroom	Companionway Saloon Galley		1,95 m 1,93 m 1,92 m		1,94 1,94 1,90	1 m

- Not available C = Cabins H = Head■ Standard □ Option



